

BS EN3&CE 产 品 数 据 表

BS EN3&CE Data Sheet

1. 产品数据表

Product data sheet

产品名称 Product Name	产品技术参数 Product Technical Data	
5kg BSI EN3&CE 二 氧化碳灭火器 5kg BSI EN3&CE CO2 fire extinguisher Model Number: MT5 Dehuan KM784887	瓶体尺寸: D136mm×H655mm	Cylinder Size: D136mm×H655mm
	容积: 7.5 L	Volume: 7.5L
	最小壁厚: 2.9mm	Min Wall Thickness: 2.9mm
	二氧化碳灌冲量: >4.9kg	Filling With: >4.9kg
	灭火器整机重量: 17.5kg	Fire Extinguisher N.W: 17.5kg
	灭火器尺寸: 20×15×75cm	Fire Extinguisher Meas: 20×15×75cm
	温度范围: -20°C~+60°C	Temperature Range: -20°C~+60°C
	工作压力: 17.4Mpa	Working Pressure: 17.4Mpa
	测试压力: 29Mpa	Test Pressure: 29Mpa
	灭火等级 89B	Fire Rate: 89B
Carton Package: 15×20×75cm/pc UN No.1044, Class 2.2		

2. 上述产品系 34CrMo4 板材拉伸焊接产品。

The fire extinguisher mentioned above is stretch-welding products by 34CrMo4 Steel.

3. 所使用材料（钢板材、焊丝、瓶口、表面喷涂）均对人体无毒害作用。

The material(steel plate, welding wire, nick ring and electro-painting coating) are no poison to human body.

4. 产品组装焊接公差按国际标准 IT15 执行。

Welding and assembling tolerance reference by IT15.

5. 产品配置灭火药剂为二氧化碳。

Filled with CO2 gas.

6. 产品数据有效期 6 年，产品质量保证 4 年(除人为或其他意外事故导致的瓶体破损、磨损致使产品丧失承压性能除外)。产品认证标准: BS EN3-7

PDS valid for 6 years, product quality warranty for 4 years (except for man-made or other accidents caused cylinder broken, abrasion resulting to the cylinder loss its base anti-pressure capacity). Products approved by BS EN3-7.

7. 产品储运时避免环境温度长期高于 60 摄氏度且避免阳光直射。运输时需按照 2.2 类危险品运输，注意不要用尖锐物体撞击刺穿瓶体。

Avoid long-term store in the environment temperature higher than 60°C and avoid direct sunlight. Transportation is required to deal as IMO class 2.2 dangerous goods, sharp object hit the cylinder is absolutely avoided.