

## BS EN3&CE 产 品 数 据 表

### BS EN3&CE Data Sheet

#### 1. 产品数据表

##### Product data sheet

产品名称 Product Name	产品技术参数 Product Technical Data	
50kg BSI EN3&CE 干粉灭火器 50kg BSI EN3&CE dry powder fire extinguisher Model Number: P50A <b>Orientx</b> KM665805	瓶体尺寸: D300mm×H919mm	Cylinder Size: D300mm×H919mm
	最小壁厚: 2mm	Min Wall Thickness: 2mm
	干粉灌冲量: 50kg	Filling With: 50kg
	灭火器整机重量: 79kg	Fire Extinguisher N.W: 79kg
	灭火器尺寸: 45×39×112cm	Fire Extinguisher Meas: 45×39×112cm
	温度范围: -20°C~+60°C	Temperature Range: -20°C~+60°C
	工作压力: ≤1.8Mpa	Working Pressure: ≤1.8Mpa
	测试压力: 2.7Mpa	Test Pressure: 2.7Mpa
	灭火等级: A & IVB	Fire Rate: A & IVB
	Carton Package: 45×39×112cm/pc UN No.1044, Class 2.2	

#### 2. 上述产品系 DC01 板材拉伸焊接产品。

The fire extinguisher mentioned above is stretch-welding products by DC01.

#### 3. 所使用材料（钢板材、焊丝、瓶口、表面喷涂）均对人体无毒害作用。

The material(steel plate, welding wire, nick ring and electro-painting coating) are no poison to human body.

#### 4. 产品组装焊接公差按国际标准 IT15 执行。

Welding and assembling tolerance reference by IT15.

#### 5. 产品配置灭火药剂干粉为 EN615 标准 ABC 类，含量 40%；驱动气体为>99%的氮气气体 Filled with EN615 approved ABC 40% dry powder fire extinguish agent; charged with 99% nitrogen gas.

#### 6. 产品数据有效期 6 年，产品质量保证 4 年(除人为或其他意外事故导致的瓶体破损、磨损致使产品丧失承压性能除外)。产品认证标准: BS EN3-7

PDS valid for 6years, product quality warranty for 4 years (except for man-made or other accidents caused cylinder broken, abrasion resulting to the cylinder loss its base anti-pressure capacity). Products approved by BS EN3-7.

#### 7. 产品储运时避免环境温度长期高于 60 摄氏度且避免阳光直射。运输时需按照 2.2 类危险品运输，注意不要用尖锐物体撞击刺穿瓶体。

Avoid long-term store in the environment temperature higher than 60°C and avoid direct sunlight. Transportation is required to deal as IMO class 2.2 dangerous goods, sharp object hit the cylinder is absolutely avoided.